

## A Grade Premium Unleaded Gasoline Specifications

(Conventional Gasoline - This product does not meet the requirements for reformulated gasoline and may not be used in any reformulated gasoline covered area.)

Product Property	Test Method	Origin		Deliveries <sup>1/</sup>
		Minimum	Maximum	
Gravity, ° API	D287	Report		
Color		Undyed		
Volatility <sup>2/</sup>				
Benzene, vol %	D3606		4.9	
Mercaptan Sulfur, wt % <sup>3/</sup>	D3227		0.003	
Copper Corrosion	D130		1	
Silver Corrosion	D7667, 7671		1	
Gum, Existent, mg/100 ml	D381		4	5
Oxidation Stability, minutes	D525	240		
Phosphorus, g/gal	D3231		0.003	0.005
Lead, g/gal	D3237		0.010	0.05
Octane				
RON	D2699		Report	
MON	D2700		Report	
(R+M)/2		91.0		
Sulfur, ppm	D2622		80	
Oxygenates, vol%	D4815, D5599		0.05	
Haze Rating <sup>4/</sup>	D4176		2	3
NACE Corrosion	TM0172, D7548	B+		
Odor <sup>5/</sup>		Nonoffensive		

1/ Delivered products meets all applicable requirements at time and place of delivery.

2/ Refer to Seasonal Gasoline Volatility Schedule.

3/ Mercaptan Sulfur determination is waived if the result of the Doctor Test ASTM D4952 is negative.

4/ Compliance with ASTM D4176 will be determined using Procedure 2 at the following temperatures, adjusted seasonally:

February 16 – September 30                      55 °F max

October 1– February 15                              45 °F max

5/ Any gasoline exhibiting an offensive odor and/or containing more than 0.30 wt % dicyclopentadiene will not be accepted for shipment.